



Coupling	Torque (in-lbs)	Diameter (in)	Weight (lbs)	Std Max Bore (in)	Spec Max Bore (in)	Torque (in-lbs)/Weight (lbs)
XTSR52-726	2,630	3.74	3.90	1.75	2.38	674
XTSR71-726	2,630	3.74	6.83	1.63	2.38	385
<b>PSC 57-516</b>	<b>3,000</b>	<b>2.73</b>	<b>2.28</b>	<b>1.50</b>	<b>2.63</b>	<b>1,315</b>
XTSR52-826	4,900	4.25	7.40	2.00	2.88	662
XTSR71-826	4,900	4.25	11.00	2.00	2.88	445
<b>PSC 57-696</b>	<b>7,000</b>	<b>3.50</b>	<b>5.08</b>	<b>2.00</b>	<b>3.38</b>	<b>1,378</b>
XTSR52-996	8,210	5.08	10.50	2.25	3.38	782
XTSR71-996	8,210	5.08	18.50	2.38	3.38	444
<b>PSC 57-906</b>	<b>16,000</b>	<b>4.64</b>	<b>11.37</b>	<b>2.50</b>	<b>4.25</b>	<b>1,407</b>
XTSR52-1088	19,400	5.51	18.40	2.50	4.00	1,054
XTSR71-1088	19,400	5.51	27.60	2.88	4.00	703
XTSR52-1298	31,400	6.54	29.90	3.00	4.50	1,050
XTSR71-1298	31,400	6.54	45.40	3.38	4.50	692
<b>PSC 57-1058</b>	<b>33,000</b>	<b>5.33</b>	<b>18.01</b>	<b>3.00</b>	<b>5.00</b>	<b>1,832</b>
XTSR52-1548	52,300	7.76	45.90	3.50	5.00	1,139
XTSR71-1548	52,300	7.83	76.30	4.00	5.00	685
<b>PSC 57-1358</b>	<b>66,000</b>	<b>6.89</b>	<b>35.10</b>	<b>4.00</b>	<b>6.50</b>	<b>1,880</b>
XTSR52-1698	72,500	8.58	63.90	4.00	5.50	1,135
XTSR71-1698	72,500	8.66	104.00	4.50	5.50	697
XTSR52-1928	98,200	9.65	84.20	4.50	6.00	1,166
XTSR71-1928	98,200	9.66	138.00	5.00	6.00	712
XTSR52-2068	136,000	10.39	110.00	4.75	6.50	1,236
XTSR71-2068	136,000	10.39	187.00	5.50	6.50	727
<b>PSC 57-1708</b>	<b>142,500</b>	<b>8.79</b>	<b>75.36</b>	<b>5.00</b>	<b>8.00</b>	<b>1,891</b>
XTSR52-2278	176,000	11.46	154.00	5.38	7.75	1,143
XTSR71-2278	176,000	11.44	243.00	6.00	7.75	724
XTSR52-2468	232,000	12.32	192.00	5.75	8.63	1,208
XTSR71-2468	232,000	12.32	315.00	6.50	8.63	737
<b>PSC 57-2048</b>	<b>264,000</b>	<b>10.65</b>	<b>133.14</b>	<b>6.00</b>	<b>10.00</b>	<b>1,983</b>

Coupling	Torque (in-lbs)	Diameter (in)	Weight (lbs)	Std Max Bore (in)	Spec Max Bore (in)	Torque (in-lbs)/Weight (lbs)
XTSR52-2698	318,000	13.50	245.00	6.00	9.13	1,298
XTSR71-2698	318,000	13.58	406.00	7.75	9.13	783
XTSR52-2888	416,000	14.61	331.00	6.75	10.00	1,257
XTSR71-2888	416,000	15.00	567.00	8.63	10.00	734
XTSR52-3058	461,000	15.55	380.00	7.13	11.00	1,213
XTSR71-3058	461,000	15.94	604.00	9.13	11.00	763
<b>PSC 57-2558</b>	<b>474,000</b>	<b>13.18</b>	<b>238.97</b>	<b>7.00</b>	<b>12.50</b>	<b>1,984</b>
XTSR52-3358	622,000	16.81	512.00	8.00	11.50	1,215
XTSR71-3358	622,000	17.20	807.00	10.00	11.50	771
XTSR52-3668	834,000	18.35	725.00	8.88	12.25	1,150
XTSR71-3668	834,000	18.98	1150.00	11.00	12.25	725
XTSR52-3908	909,000	19.29	840.00	9.50	14.00	1,082
XTSR71-3908	909,000	19.80	1180.00	11.50	14.00	770
<b>PSC 57-3008</b>	<b>950,000</b>	<b>15.47</b>	<b>429.75</b>	<b>8.25</b>	<b>14.00</b>	<b>2,211</b>
XTSR52-4178	1,130,000	20.63	1030.00	10.13	15.00	1,097
XTSR71-4178	1,130,000	20.83	1430.00	12.25	15.00	790
<b>PSC 57-3438</b>	<b>1,500,000</b>	<b>17.63</b>	<b>627.99</b>	<b>9.75</b>	<b>17.00</b>	<b>2,389</b>
XTSR52-4588	1,670,000	23.11	1460.00	11.00	16.00	1,144
XTSR71-4588	1,670,000	23.94	2190.00	14.00	16.00	763
XTSR52-4918	2,080,000	24.80	1800.00	11.75	16.00	1,156
XTSR71-4918	2,080,000	25.51	2650.00	15.00	16.00	785
<b>PSC 57-4048</b>	<b>2,250,000</b>	<b>20.88</b>	<b>1080.00</b>	<b>12.00</b>	<b>20.00</b>	<b>2,083</b>
XTSR52-5258	2,510,000	26.46	2190.00	12.63	16.00	1,146
XTSR71-5258	2,510,000	26.69	3130.00	16.00	16.00	802
<b>PSC 57-4848</b>	<b>3,500,000</b>	<b>24.63</b>	<b>1850.00</b>	<b>14.00</b>	<b>23.00</b>	<b>1,892</b>

\* Based on data published as of September 1, 2017

- ✓ Competitor couplings can weigh 3x as much as the comparable PSC model
- ✓ The PSC model offers lower mass, better balance, and allows for much longer life of connected equipment