



Coupling	Torque (in-lbs)	Diameter (in)	Weight (lbs)	Std Max Bore (in)	Spec Max Bore (in)	Torque (in-lbs)/ Weight (lbs)
KD21 - 053	2,000	3.94	7.7	1.75		260
<b>PSC 57-516</b>	<b>3,000</b>	<b>2.73</b>	<b>2.3</b>	<b>1.50</b>	<b>2.63</b>	<b>1,315</b>
KD21 - 103	4,000	3.94	7.8	1.75		513
<b>PSC 57-696</b>	<b>7,000</b>	<b>3.50</b>	<b>5.1</b>	<b>2.00</b>	<b>3.38</b>	<b>1,378</b>
KD21 - 153	13,600	5.38	17.7	2.50		768
<b>PSC 57-906</b>	<b>16,000</b>	<b>4.64</b>	<b>11.4</b>	<b>2.50</b>	<b>4.25</b>	<b>1,407</b>
<b>PSC 57-1058</b>	<b>33,000</b>	<b>5.33</b>	<b>18.0</b>	<b>3.00</b>	<b>5.00</b>	<b>1,832</b>
KD20 - 204	36,000	6.62	39.2	3.25	4.62	918
KD21 - 204	36,000	6.38	29.8	3.00		1,208
KD20 - 254	52,000	7.88	61.2	4.00	5.62	850
KD21 - 254	52,000	7.62	44.3	3.75		1,174
<b>PSC 57-1358</b>	<b>66,000</b>	<b>6.89</b>	<b>35.1</b>	<b>4.00</b>	<b>6.50</b>	<b>1,880</b>
KD20 - 304	89,000	9.25	104.0	4.75	6.50	856
KD21 - 304	89,000	9.00	70.4	4.50		1,264
<b>PSC 57-1708</b>	<b>142,500</b>	<b>8.79</b>	<b>75.4</b>	<b>5.00</b>	<b>8.00</b>	<b>1,891</b>
KD20 - 354	150,000	10.75	172.0	5.50	7.62	872
KD21 - 354	150,000	10.50	117.0	5.00		1,282
KD20 - 404	215,000	12.00	251.0	6.25	8.75	857
KD21 - 404	215,000	11.75	177.0	5.50		1,215
KD20 - 454	255,000	13.00	302.0	7.25	9.38	844
KD21 - 454	255,000	12.75	205.0	6.38		1,244
<b>PSC 57-2048</b>	<b>264,000</b>	<b>10.65</b>	<b>133.1</b>	<b>6.00</b>	<b>10.00</b>	<b>1,983</b>

Coupling	Torque (in-lbs)	Diameter (in)	Weight (lbs)	Std Max Bore (in)	Spec Max Bore (in)	Torque (in-lbs)/ Weight (lbs)
KD20 - 504	360,000	14.12	427.0	7.50		843
KD21 - 504	360,000	13.88	305.0	7.00		1,180
<b>PSC 57-2558</b>	<b>474,000</b>	<b>13.18</b>	<b>239.0</b>	<b>7.00</b>	<b>12.50</b>	<b>1,984</b>
KD20 - 554	505,000	15.38	569.0	8.25		888
KD21 - 554	505,000	15.12	402.0	7.75		1,256
KD20 - 604	660,000	16.88	777.0	9.00		849
KD21 - 604	660,000	16.50	512.0	8.50		1,289
<b>PSC 57-3008</b>	<b>950,000</b>	<b>15.47</b>	<b>429.8</b>	<b>8.25</b>	<b>14.00</b>	<b>2,211</b>
<b>PSC 57-3438</b>	<b>1,500,000</b>	<b>17.63</b>	<b>628.0</b>	<b>9.75</b>	<b>17.00</b>	<b>2,389</b>
KD20 - 705	1,510,000	20.88	1360.0	10.88		1,110
KD21 - 705	1,510,000	20.50	922.0	10.75		1,638
<b>PSC 57-4048</b>	<b>2,250,000</b>	<b>20.88</b>	<b>1080.0</b>	<b>12.00</b>	<b>20.00</b>	<b>2,083</b>
KD20 - 805	2,310,000	23.38	2060.0	12.25		1,121
KD21 - 805	2,310,000	23.00	1350.0	12.00		1,711
KD20 - 905	2,600,000	25.88	2490.0	13.50		1,044
KD21 - 905	2,600,000	25.50	1700.0	13.50		1,529
<b>PSC 57-4848</b>	<b>3,500,000</b>	<b>24.63</b>	<b>1850.0</b>	<b>14.00</b>	<b>23.00</b>	<b>1,892</b>

\* Based on data published as of September 1, 2017

- ✓ Competitor couplings weigh significantly more than the comparable PSC model
- ✓ The PSC model offers lower mass, better balance, and allows for much longer life of connected equipment